



Global Sealer
Technologies

**Elephant
Armor™**



Elephant Armor Cure and Hardener

FOR USE ON:

- Curbs, Pothole and Spall Repairs
- Overlays
- Concrete Slabs
- Sidewalks and Driveways
- Concrete Columns and Beams

FEATURES:

- Dries to a clear membrane
- No unsightly yellow/amber residue
- Ensures proper curing, resulting in stronger, more wear resistant concrete
- Helps minimize dusting
- Once cure membrane dissipates or has been removed, substrate is compatible with most paints, sealers, coating and floor covering adhesives

www.gstinternational.com

Elephant Armor™ Cure and Hardener

PRODUCT INFORMATION:

Elephant Armor Cure is a clear, dissipating resin water-based emulsion curing compound for use on freshly finished horizontal and vertical concrete surfaces. Elephant Armor Cure is formulated to provide an effective curing membrane that will dry to a clear (nonyellowing) membrane. Elephant Armor Cure will provide a more cost effective alternative to cure & seals without the unsightly yellow/amber appearance of other dissipating resins.

IMPORTANT NOTE: Before use on a job, thoroughly test this product on a sample to assure performance and appearance. Do not apply if the temperature of the surface is less than 40°F. If **Elephant Armor Cure** is accidentally spilled or sprayed on glass, brick, aluminum, or painted surfaces immediately flush with water.

If you are using Elephant Armor for decorative concrete overlay and will be applying color or a sealer, DO NOT USE Elephant Armor Cure, as it will block penetration of these materials.

APPLICATION: Agitate thoroughly before use. Application equipment must be clean and free of foreign materials. Elephant Armor Cure appears milky white in the container and during application, but will dry to a clear film. A spray application using GST International's 2 Gallon Pump Up Sprayer is the preferred method. Application temperatures above 40°F (4°C) are recommended. Areas that are to be caulked should be masked. Do not pool or puddle.

COVERAGE: Coverage will vary depending on the texture and porosity of the concrete. Apply at a rate of 200-400 ft²/gal immediately after final trowel.

DRYING TIME: Depending on porosity of the surface and weather conditions, usually one hour.

DRY SCHEDULE: To Touch 1 Hour
..... Rainproof/Cured 24 hours

PACKAGING:

- 1 gal (3.8 L) plastic containers

CLEAN UP: Soap and water

SPECIFICATIONS / COMPLIANCES: Formulated to comply with ASTM C-309, Types 1 and 1D, Class A & B. AASHTO M-148, Type 1, Class A & B

KEEP FROM FREEZING

SDS available at www.gstinternational.com

FOR PROFESSIONAL USE ONLY

SHIPPING & HMIS INFORMATION:

VOC: <100 g/l

FLASH POINT: N/A

SHIPPING INFORMATION: Ground/Air Vessel Not regulated

Required Label: None

Required Marking: None

UNIFORM FIRE CODE: Not Combustible

STORAGE TEMPERATURE: 35°-120°F (1°-49°C).

SHELF LIFE: Warranted 1 year

HMIS RATINGS: H - 2; F - 0; R - 0; PP - H

SAFETY PRECAUTIONS:

- Residual membrane must be thoroughly removed prior to painting, topping, or any subsequent treatment.
- Do not apply at temperatures below 40°F (4°C).
- Do not dilute or alter in any way.
- Always follow subsequent coating manufacturers' recommendations for surface preparation.
- Keep out of the reach of children.
- Do not take internally.
- If ingested, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- Can cause skin irritation upon contact, especially prolonged or repeated. If skin contact occurs, wash immediately with soap and water and seek medical help as needed.
- If eye contact occurs, flush immediately with clean water and seek medical help as needed.
- Read SDS before using product.

This product is made from the finest raw materials available and manufactured to proven formulation under strict quality control for its intended use. However, results obtained with the use of this product under a variety of conditions may depend on circumstances beyond our control. GST International, Inc. and the seller therefore disclaim any responsibility for damage of any kind. The only warranty extended, expressed or implied, is for defective material.

MANUFACTURED IN THE USA